



JM-LG01 is an asset tracking solution that allows you to locate, monitor and optimize your non-powered assets. With a battery life of up to 3 years (WiFi position only), you can stick it on just about anything you want to keep track of.





GPS & WiFi & LBS Positioning

A synergy of multiple positioning systems ensures that locations are accurately displayed on the cloud platform.



Intelligent Power Management

Automatically adjust the working status for saving power without affecting normal functioning.



Tamper Alert

Receive a tamper alert when the light sensor detects device removal.



IPX5 Water Resistance

Rugged design ensures continued optimal performance, even in the toughest conditions.



2,800mAh Disposable Battery

Special processing of disposable battery enables a relatively longer lifespan.



Strong Magnetic Mount

Near-zero installation; the LG01 tightly and effortlessly fastens to most metal surfaces.







GNSS

| Positioning system | GPS+WiFi+LBS |
|-------------------------|--|
| Frequency | L1 |
| Positioning accuracy | < 2.5m CEP |
| Track sensitivity | -165dBm |
| Acquisition sensitivity | -148dBm |
| TTFF (open sky) | Avg, hot start ≤1sec Avg. cold start ≤32sec |

Cellular

| Communication network | GSM |
|-----------------------|---------------------------------|
| Frequency | Quad-band 850/900/1800/1900 MHz |

Power

| Battery | 2,800mAh/3.0V industrial-grade Li-Manganese battery |
|---------------|---|
| Working modes | Mode 1: Tracking mode |
| | Mode 2: Power-Saving mode |
| | Mode 3: Week-based mode |
| | Mode 4: Alarm-based mode |
| Standby time | Up to 3 years (one fix per day) |

Interface

| LED indication | 1 working status indicator (Red) |
|----------------|----------------------------------|
| SIM | Micro-SIM |
| Data storage | 32+32Mb |
| Tamper proof | Light sensor |

Physical specification

| Dimensions | 82.0 x 42.0 x 20.0mm |
|------------|----------------------|
| Weight | 72g |

Operating environment

| Operating temperature | -20°C to +70°C |
|-----------------------|------------------------|
| Operating humidity | 5%~95%, non-condensing |
| IP rating | IPX5 |

Feature

| Sensors | Accelerometer, Light sensor |
|-----------|--|
| Scenarios | Low battery alert, Tamper alert, Geo-fence |